

## PRODUCT INFORMATION SHEET

### Red laser level



#### Product description

Professional self-leveling cross line and side laser level, for precise defining of the vertical and horizontal cross line, vertical side line, and horizontal and vertical cross line, and vertical side line with a laser beam. Its application ensures the highest precision of measurement and the elimination of errors in renovation and construction, finishing, assembly and installation works. It is also applicable to decorating works, e.g. hanging shelves or paintings. It can be used both indoors and outdoors.

#### Characteristics

- high self-leveling accuracy +/- 3.5°, manual adjustment is not required;
- working range: beam up to 12 m / diameter up to 24 m;
- red laser beam ensures legibility and clarity of reading;
- self-leveling lock increases the comfort of work;
- 3 measurement options: horizontal and vertical; horizontal and vertical & side vertical line, side vertical line;
- measurement accuracy at the level of 0.7 mm/m;
- laser wavelength 635 Nm;
- class II accuracy;
- 1/4" tripod thread;
- IP54 rating will ensure protection against dust and water;
- working time up to 8 hours;
- additional holder with a magnet that makes it possible to fix the level, for example to a steel profile;
- powered by 2 x AA 1.5V batteries;
- compact size and low weight ensure easy storage and transport of the level, which can be a basic equipment of a tool box;
- packed in a practical case that protects the product against dirt and damage.

#### Technical data

|         |               |            |   |    |
|---------|---------------|------------|---|----|
|         |               |            |   |    |
| HT4M071 | 5902801331459 | up to 24 m | 1 | 10 |

|           |           |           |                       |               |         |           |
|-----------|-----------|-----------|-----------------------|---------------|---------|-----------|
| RED LASER | AUTO±3.5° | AUTO LOCK | Cross & Side vertical | Side vertical | Cross   | ±0,7 mm/m |
| 635Nm     | CLASS II  | 2xAA 1,5V | 1/2"                  | IP54          | max 8 h | HOLDER    |

Högert Technik GmbH, Pariser Platz 6a, 10117 Berlin, Deutschland  
 Producent/Manufacturer/Hersteller/Произведено  
 для:  
 PL GTV Poland S.A., ul. Przejazdowa 21 05-800 Pruszków, Polska/ Poland/ Polen/ Польша  
 Importer/ Импортёр:  
 RU ООО «ГТВ РУС» 140073, Московская область, город Люберцы, рабочий поселок Томилино, микрорайон Птицефабрика, литер 7А; info@hoegert.ru  
 HR GTV Croatia d.o.o.; Kovinska 4s, 10000 Zagreb, Hrvatska  
 Distributor:  
 ES GTV España Herrajes, E Iluminación, S.L., Avenida Aragón 308, 46021 Valencia, Spain  
 CZ GTV Czech Distribution s.r.o., CTPark Ostrava, Na Rovince 879, 720 00 Ostrava Hrabová